Predefined PL/SQL Exceptions

An internal exception is raised implicitly whenever your PL/SQL program violates an Oracle rule or exceeds a system-dependent limit.

PL/SQL declares predefined exceptions globally in package STANDARD, which defines the PL/SQL environment. So, you need not declare them yourself and write handlers for predefined exceptions using the names in the following list:

Exception	Raised when
ACCESS_INTO_NULL	Your program attempts to assign values to the attributes of an uninitialized
	(atomically null) object.
CASE_NOT_FOUND	None of the choices in the WHEN clauses of a CASE statement is selected, and there
	is no ELSE clause.
COLLECTION_IS_NULL	Your program attempts to apply collection methods other than EXISTS to an
	uninitialized (atomically null) nested table or varray, or the program attempts to
	assign values to the elements of an uninitialized nested table or varray.
CURSOR_ALREADY_OPEN	Your program attempts to open an already open cursor. A cursor must be closed
	before it can be reopened. A cursor FOR loop automatically opens the cursor to
	which it refers. So, your program cannot open that cursor inside the loop.
DUP_VAL_ON_INDEX	Your program attempts to store duplicate values in a database column that is
	constrained by a unique index.
INVALID_CURSOR	Your program attempts an illegal cursor operation such as closing an unopened
	cursor.
INVALID_NUMBER	In a SQL statement, the conversion of a character string into a number fails because
	the string does not represent a valid number. (In procedural statements,
	VALUE_ERROR is raised.) This exception is also raised when the LIMIT-clause
	expression in a bulk FETCH statement does not evaluate to a positive number.
LOGIN_DENIED	Your program attempts to log on to Oracle with an invalid username and/or password.
NO_DATA_FOUND	A SELECT INTO statement returns no rows, or your program references a deleted
	element in a nested table or an uninitialized element in an index-by table. SQL
	aggregate functions such as AVG and SUM always return a value or a null. So, a
	SELECT INTO statement that calls an aggregate function never raises
	NO_DATA_FOUND. The FETCH statement is expected to return no rows eventually,
	so when that happens, no exception is raised.
NOT_LOGGED_ON	Your program issues a database call without being connected to Oracle.
PROGRAM_ERROR	PL/SQL has an internal problem.
ROWTYPE_MISMATCH	The host cursor variable and PL/SQL cursor variable involved in an assignment have
	incompatible return types. For example, when an open host cursor variable is passed
	to a stored subprogram, the return types of the actual and formal parameters must
	be compatible.

SELF_IS_NULL	Your program attempts to call a MEMBER method on a null instance. That is, the built-in parameter SELF (which is always the first parameter passed to a MEMBER method) is null.
STORAGE_ERROR	PL/SQL runs out of memory or memory has been corrupted.
SUBSCRIPT_BEYOND_COUNT	Your program references a nested table or varray element using an index number larger than the number of elements in the collection.
SUBSCRIPT_OUTSIDE_LIMIT	Your program references a nested table or varray element using an index number (-1 for example) that is outside the legal range.
SYS_INVALID_ROWID	The conversion of a character string into a universal rowid fails because the character string does not represent a valid rowid.
TIMEOUT_ON_RESOURCE	A time-out occurs while Oracle is waiting for a resource.
TOO_MANY_ROWS	A SELECT INTO statement returns more than one row.
VALUE_ERROR	An arithmetic, conversion, truncation, or size-constraint error occurs. For example, when your program selects a column value into a character variable, if the value is longer than the declared length of the variable, PL/SQL aborts the assignment and raises VALUE_ERROR. In procedural statements, VALUE_ERROR is raised if the conversion of a character string into a number fails. (In SQL statements, INVALID_NUMBER is raised.)
ZERO_DIVIDE	Your program attempts to divide a number by zero.